- 1. (previously presented) A wear-resistant electrically conductive body, comprising:
 - (a) an electrically conductive body; and
 - (b) an ion-accelerated, wear-resistant, electrically conductive coating on the electrically conductive body, the ion-accelerated, wear-resistant, electrically conductive coating containing contiguous metal atoms and diamond-like carbon atoms.

- 2.(currently amended) A plurality of wear-resistant electrically conductive slip-rings on a rotor, comprising:
 - (a) a plurality of electrically conductive slip-rings on a rotor; and
 - (b) an ion-accelerated, wear-resistant, electrically conductive coating on each electrically conductive slip-ring, each ion-accelerated, wear-resistant, electrically conductive coating containing simultaneously ion deposited, contiguous, metal-ion-accelerated ion-accelerated metal atoms and carbon-ion-accelerated ion-accelerated diamond-like carbon atoms.

3. (currently amended) Each wear-resistant electrically conductive slip-rings of claim 2 wherein the simultaneously ion deposited, contiguous, metal-ion-accelerated ion-accelerated metal atoms are contiguous copper-ion-accelerated ion-accelerated copper atoms.

4. (previously presented) Wear resistant electrically conductive slip-rings of claim 2, each wear resistant electrically conductive slip-ring further comprising an interfacial layer between the ion-accelerated, wear resistant, electrically conductive coating and the electrically conductive slip-ring.

5. (previously presented) A method for making a wear-resistant electrically conductive body, comprising ion-accelerating copper ions and diamond-like carbon ions onto an electrically conductive body, the ion-accelerating of the copper ions and diamond-like carbon ions occurring simultaneously.

- 6. (previously presented) A wear-resistant electrically conductive body, comprising:
 - (a) an electrically conductive body; and
 - (b) an electrically conductive ion-formed diamond-like surface on the electrically conductive body, the surface containing diamond-like, amorphous carbon and graphite, the amorphous carbon and graphite being in a contiguous configuration.

- 7. (previously presented) A dual ion-beam process for depositing a wear-resistant diamond-like coating on an electrically conductive surface, comprising
 - (a) sputtering a surface of a diamond-like carbon source with first ion beam;
 - (b) striking carbon atoms that are on the electrically conductive surface with a second ion beam, in order to maintain the carbon atoms in a metastable state;
 - (c) adjusting power and intensity of the first ion beam in order to control an intensity of energy applied to the diamond-like carbon source; and
 - (d) adjusting power and intensity of the second ion beam, in order to control characteristics of a wear-resistant diamond-like coating on the electrically conductive surface.